



SNAP WRAP and MINI WRAP Connectors

CATALOG
SW-1



**240 Series 30-Contact Mini-Wrap®
(Miniature Size) Connector Pair**



**230 Series 30-Contact Snap-Wrap®
(Standard Size) Connector Pair**

**SIMPLE SOLUTION
TO MANY
COMPLEX PROBLEMS**

Snap-Wrap® (230 Series) and Mini-Wrap® (240 Series) Connectors are based on a modular design concept for which the original patents are jointly owned by AMPHENOL and Malco Manufacturing Co. of Chicago. By application of this concept, AMPHENOL's integrated and centralized facilities can be arranged to accommodate practically any configuration as a standard product. This enables AMPHENOL to produce "specials" rapidly and at low cost. Automatic check-out equipment and digital-type inspections insure high reliability.



A DIVISION OF AMPHENOL-BORG ELECTRONICS CORPORATION
1830 S. 54TH AVENUE • CHICAGO 50, ILLINOIS • AREA 312 • 242-1000 • TWX 312-656-7125

Snap-Wrap® and Mini-Wrap® Connectors

Fit Your Requirements

EXACTLY • ECONOMICALLY • QUICKLY

Modular Design Permits Any Configuration Desired

Snap-Wrap and Mini-Wrap connectors are built on a simple modular basis: Contacts are inserted into nylon bushings, and the bushings are "snapped" into punched holes in an aluminum base plate.

The base plate, available in various finishes, may be as big as 24" x 24" or as small as you want. It can be shaped, formed, notched, or have any kind of cutouts or mounting holes you need to fit your space and components. The holes may be punched (or omitted) in any configuration in a .200" x .200" grid, 21" square on Snap-Wrap, or as close as .100" x .100" on Mini-Wrap connectors.

The nylon bushings serve as both contact retention devices and as a dielectric. Available in natural translucent white, or dyed to match any color code, they come in different sizes for different contact spacings.

Many different types of male and female contacts are available for wire-wrap*, crimp, or solder connections.

This simple modular construction gives Snap-Wrap and Mini-Wrap connectors practically unlimited versatility. In fact, even after you have the finished connector, if your contact or circuit requirements change, a simple tool enables you to insert or remove bushings (with contacts) at will.

Standard Components Reduce Cost and Speed Delivery

Because special tooling is at a minimum, Snap-Wrap and Mini-Wrap connectors can be tailor-made to your layout quickly and at low cost.

Automatic Wire-Wrap* Capability Cuts Assembly Time, Increases Reliability

Snap-Wrap and Mini-Wrap connectors can be wired with programmed automatic wrapping machines—for example, the Gardner-Denver machine—at savings up to 50% compared to soldering.

What's more, chances of wiring error and bad connections are virtually eliminated. In actual usage, failures average less than 1 to 500,000. Reliability is high because wire-wrap connections are resistant to corrosive atmosphere, severe shock and vibration.

Of course, Snap-Wrap and Mini-Wrap connectors are not limited to machine wrapping. Hand wire-wrap* tools may also be used effectively. Contact terminations for crimp or solder connections are available, too, in a variety of options for fast, efficient assembly methods such as automatic crimping or dip soldering. It's a well balanced connector line with provisions for all kinds of requirements.

Precision Spacing and Interlocking Parts Provide Strength and Stability

Snap-Wrap and Mini-Wrap contacts are accurately spaced to start with, and they *stay* that way. Unlike conventional molded connectors, they do not rely on the connector body for rigidity and mechanical strength. The combination of base plate and nylon bushings offers the right balance of strength, resilience, and light weight to assure excellent stability in all sizes and configurations.


APPLICATION: WHEREVER YOU WANT LOW-COST, CUSTOM, EFFICIENT CONNECTORS—Whether it's a large area connector to eliminate a multitude of sub-assemblies (for example, a distribution center or computer programming board)—or a small odd-shaped connector to fit an irregular space—Snap-Wrap or Mini-Wrap connectors will do an excellent job.

You can use these connectors for any standard application, regular or miniature—for racks and panels—for printed circuit board connectors, headers, card cages—for plug-in modules—cable connectors—patch cord terminals and plugs. You can have jackscrews for locking action, countless polarization options—in short, practically anything you want.

HOW TO GET EXACTLY WHAT YOU WANT—Obviously, you have far too wide a range of choices in Snap-Wrap and Mini-Wrap connectors to permit selection by a simple part number system. The best way to get the exact combination of characteristics you want is to call your AMPHENOL Sales Engineer. He'll help you meet your specific requirements most efficiently.

*TM—Gardner-Denver Co.

Maximum Size Snap-Wrap Base Plate



Mini-Wrap base plates are similar but slightly smaller and with more closely spaced grids.

Base Plate Specifications

Material: Aluminum AA1100-H14 (2S)

Thickness: Snap-Wrap: .125" nominal—Mini-Wrap: .080" nominal

Maximum Size: Snap-Wrap: 24" x 24"—Mini-Wrap: 22" x 22"

Maximum Number of Holes in Maximum Size Plate:

Snap-Wrap: 11,448 Commercial Pattern
7,560 Military Pattern

Mini-Wrap: .100" Grid—26,662

.125" Grid—17,169

.150" Grid—11,988

Finish: Gold Iridite or Anodize (colors available)


Markings: Silk Screened and/or Rubber Stamping to Your Requirements

Grid Spacing Tolerance:

.003" non-cumulative up to 100 sq. in. pattern


.005" non-cumulative over 100 sq. in. pattern

Grid Systems



















NOTE: All these grid systems are recommended for programmed automatic wire wrapping. Grid system arrangements for diagonal wiring are available on the .200" x .200", .150" x .150", and .100" x .100" grids.

Typical Snap-Wrap® and Mini-Wrap® Connectors



Snap-Wrap and Mini-Wrap Contacts (and Bushings)

			
Wrapost Female Snap-Wrap	Wrapost Male Blade Snap-Wrap	Wrapost Female Mini-Wrap	Wrapost Male Blade Mini-Wrap
			
Male Crimp Snap-Wrap	Wrapost Female Printed Circuit Card Snap-Wrap	Wrapost Offset Female Printed Circuit Card Snap-Wrap	Wrapost Slotted Blade Snap-Wrap
			
Wrapost Stud Snap-Wrap	Wrapost Single End Snap Wrap	Wrapost Double End Snap-Wrap	Wrapost Crimp Snap-Wrap
			
Wrapost Hermaphrodite Female-to-Male Snap-Wrap	P.C.B. Male Right Angle Round Tip Snap-Wrap	Wrapost Male Right Angle P.C.B. Rectangular Tip Snap-Wrap	P.C.B. Male Right Angle Mini-Wrap

NOTE: Due to the critical importance of accurate terminal positioning, all assembly of Snap-Wrap and Mini-Wrap connectors must be performed at AMPHENOL. Unassembled contacts, bushings, and contact-bushing sub-assemblies are available only for repair, replacement, evaluation, or engineering prototype purposes.


Contact Specifications

Current Rating: Snap-Wrap: 5 amps—Mini-Wrap: 3 amps
 Working Voltage: Snap-Wrap: 880 VAC—Mini-Wrap: 300 VAC
 Dry Circuitry: .1 microvolt at 10 milliamperes
 Breakdown Voltage: Snap-Wrap: Approx. 3KV contact to contact
 2.5KV contact to shell
 Mini-Wrap: Approx. 2.5 KV contact to contact
 1.5KV contact to shell
 Contact Resistance: Below .002 ohms
 Insulation Resistance: 1,000,000 megohms min. (Snap-Wrap & Mini-Wrap)
 Max. Operating Temperature, Continuous: 95°C
 Wire Size: #26 to #16 (Snap-Wrap)
 #32 to #22 (Mini-Wrap)


Material: Male Wire-Wrap: Brass per QQ-W-321
 Male Crimp: Cadmium Copper 1/8" Hard
 Female: Heat Treated Beryllium Copper per QQ-C-533 or Phosphor Bronze per QQ-P-330
 Wrapost Stud: Brass per QQ-W-321
 Finish: ① .000050 min. Gold per OS-10952 over .00020 min. Silver per QQ-S-365
 ② .00003 min. Gold per MIL-G-45204, Type II over .00020 min. Silver per QQ-S-365
 ③ Gold Flash .000020 min. over Copper Strike
 ④ Gold Flash .000020 min. over .00010 Nickel
 Bushing: Polyamide (Nylon) per MIL-M-20693A Type I

Contact Dimensions


Inches




Wrapost Female Snap-Wrap




Wrapost Male Blade Snap-Wrap




Wrapost Female Mini-Wrap




Wrapost Male Blade Mini-Wrap




Male Crimp Snap-Wrap




Wrapost Female Printed Circuit Card Snap-Wrap




Wrapost Offset Female Printed Circuit Card Snap-Wrap




Wrapost Slotted Blade Snap-Wrap



Wrapost Stud Snap-Wrap




Wrapost Single End Snap Wrap




Wrapost Double End Snap-Wrap


A DIM.	B DIM.	C DIM.
1.587	.625	.733
1.462	.500	.608
1.430	.468	.576
1.337	.375	.483
1.212	.250	.358
1.587	.625	.733
1.462	.500	.608
1.430	.468	.576
1.337	.375	.483
1.212	.250	.358




Wrapost Crimp Snap-Wrap




Wrapost Hermaphrodite Female-to-Male Snap-Wrap



P.C.B. Male Right Angle Round Tip Snap-Wrap




Wrapost Male Right Angle P.C.B. Rectangular Tip Snap-Wrap




P.C.B. Right Angle Prebent Mini-Wrap

Printed Circuit Board Headers




Snap-Wrap P.C.B. Header





Mini-Wrap P.C.B. Header

Available with 2, 3, or 4 rows of standard or miniature contacts, these sturdy aluminum headers accommodate printed circuit boards $\frac{1}{16}$ ", $\frac{3}{32}$ ", or $\frac{1}{8}$ " thick. The contacts are non-floating and mate accurately with panel board receptacles.

Printed Circuit Board Receptacles and Mini-Wrap Plugs




Snap-Wrap P.C.B. Receptacle




Mini-Wrap P.C.B. Receptacle

A
.250
.375
.500
.625
.750



Printed Circuit Board Card Cages



By simple forming of Snap-Wrap or Mini-Wrap base plates, AMPHENOL is able to supply economical card cages for your printed circuit board modules. The modular construction provides full freedom of choice in number of contacts per row and number of rows. Receptacle con-


nectors can be provided for direct entry of boards or for boards mounted to headers.

Card cages are furnished ready for wiring and mounting, with contacts and card guides completely assembled. The rugged construction and the accurate placement of contacts and guides assure positive alignment.



Program Board Connectors

Patch Board and Cord Terminals



The Snap-Wrap principle is a natural for computer programming boards, and Snap-Wrap bushings and contacts serve excellently as patch board and patch cord terminals. Three different types of pairs are available. The crimp type terminals can be furnished in chain form for automatic crimping.




Female Wrapost Board Terminal
Male Crimp Cord Terminal



Male Wrapost Board Terminal
Female Receptacle Cord Terminal





Male Wrapost Board Terminal
Receptacle Cord Terminal



Programmed Cable Connectors



Featuring a removable header plate in a lightweight, rugged aluminum housing equipped with a cable clamp, the programmed cable connector provides 20 to 100 Snap-Wrap contacts. Dimensions of the connector for various numbers of contacts are shown below.



Dimensions—Inches

Contacts	A
20	.540
30	.740
40	.940
50	1.140
60	1.340
70	1.540
80	1.740
90	1.940
100	2.140

Polarization



Every contact in a Snap-Wrap or Mini-Wrap connector can serve as a polarization guide, since it can be inserted at right angles to the normal contact pattern in the plate. Thus, there can be many polarizing combinations.

Another polarization method is to use programming keys—circular metal bushings with a keyway cut down one side to accept a keyed male pin or keying washer positioned inside the programmed cable connector. Polarization can also be achieved by using various sized guide pins.

Manual Insertion and Removal of Contacts


Individual contacts can be readily inserted or removed by use of a simple hand tool with adapters for the various contact types.

**COMPLETE SNAP-WRAP CABLE ASSEMBLIES
ARE READILY AVAILABLE—LET US KNOW OF
YOUR REQUIREMENTS.**

Poke Home Contact Crimping Tools




Positioner
See Table Below




MS 3191-1

294-126




294-605



294-506

Manual Insertion and Removal Tool



Adapter (see table below)

294-1048 Handle

ADAPTERS

Part Number		Application			
Complete Tool Adapter and Handle	Adapter Only	Configuration	Contact Type	Number	Insulation
294-138-06	294-1047-06		Insertion Tool for Ship-JP	230-201; -338	
294-138-05	294-1047-05		Removal Tool for Male Crimp	23-0263	
294-138-43	294-1047-43		Insertion Tool for Male Crimp	230-263	For .120 O.D. Wire Insulation
294-138-42	294-1047-42		Insertion Tool for Male Crimp	230-263	For .085 O.D. Wire Insulation
294-138-41	294-1047-41		Insertion Tool for Male Crimp	230-263	For .070 O.D. Wire Insulation
294-138-03	294-1047-03		Insertion Tool for Male	230-282-00; 230-287; 230-273-00	
294-138-22	294-1047-22		Removal Tool for Wire Wrap- Tails	230-202-00; 230-201; 230-273-00; 230-287; 230-288; -338	1/2" or Longer Wire Wrap*
294-138-21	294-1047-21		Removal Tool for Wire Wrap- Tails	230-202-00; 230-201; 230-273-00; 230-287; 230-288; -338	3/8" or Shorter Wire Wrap*
294-138-01	294-1047-01		Insertion Tool for Female	230-202-00; 230-288	
Use with 294-126 Crimp Tool	294-1037-01		Male Crimp	230-263	22-24-26 GA.
	294-1037-02		Male Crimp	230-286	16-18-20 GA.

*TM Gardner-Denver Co.



A DIVISION OF AMPHENOL-BORG ELECTRONICS CORP.

1830 South 54th Avenue • Chicago 50, Ill.

Phone 312 • 242-1000

AMPHENOL WESTERN—DISTRICT SALES OFFICES

CALIFORNIA	LOS ANGELES	Amphenol District Sales Office Wm. Monteforte	17000 Ventura, Suite 306 (Encino)	213 STate 8-8560
	SAN DIEGO	Amphenol District Sales Office Richard Colt	5054 Lincoln St. (La Mesa)	714 HOpkins 3-9331
	SAN FRANCISCO	Amphenol District Sales Office Donn Moore	1826 Industrial Way, Suite 8 (Redwood City)	415 369-2981
COLORADO	DENVER	Amphenol District Sales Office Keith Lusk	709 W. Littleton Blvd., Suite 200A (Littleton)	303 794-4269
HAWAII	HONOLULU 14	Donn H. Burcham Co.	949 McCully St.	993-149
WASHINGTON	SEATTLE	Amphenol District Sales Office Jim Clarizio	14444 Sunset Highway, P.O. Box 726 (Bellevue)	206 SHerwood 6-5363

AMPHENOL MIDWESTERN—DISTRICT SALES OFFICES

ILLINOIS	CHICAGO	Amphenol District Sales Office John N. Koys	2837 S. 25th Ave. (Broadview)	312 921-8670
INDIANA	INDIANAPOLIS 5	Leslie M. DeVoe Co.	4010 Washington Blvd.	317 ATwater 3-1395
MICHIGAN	DETROIT	Amphenol District Sales Office Gary A. Yeomans	960 E. Maple Rd., Suite 126 (Birmingham)	313 646-1262
MINNESOTA	MINNEAPOLIS 16	Amphenol District Sales Office Charles W. Kucera	6121 Excelsior Blvd.	612 929-7879
MISSOURI	KANSAS CITY	Amphenol District Sales Office John E. Jansen	11015 E. 39th St. Suite 5 (Independence)	816 356-5400
	ST. LOUIS	Amphenol District Sales Office Joseph Svehla	1060 Derhake Road Florissant	314 TEmple 8-6996
NEW MEXICO	ALBUQUERQUE	Albuquerque Electronics Co.	2329 Wisconsin, N.E.	505 298-2628
OHIO	CLEVELAND 16	Amphenol District Sales Office John J. Carsello	20545 Center Ridge Road, Suite 242	216 EDison 1-9100
	DAYTON 39	Amphenol District Sales Office Max F. Gray	3300 S. Dixie Drive, Room 121A	513 298-5002
TEXAS	DALLAS	Amphenol District Sales Office Edward J. Beavan	811 S. Central Expressway, Suite 200B (Richardson)	214 ADams 5-8318

AMPHENOL EASTERN—DISTRICT SALES OFFICES

DISTRICT OF COLUMBIA	WASHINGTON	Amphenol District Sales Office Stephen R. Kelleher	725 15th St., N.W. Suite 1000	202 EXecutive 3-2205
FLORIDA	WINTER PARK	Amphenol District Sales Office J. Aylward	180 Knowles Ave. Suite 9	305 647-5504
GEORGIA	ATLANTA 5	Amphenol District Sales Office Ed. Smith	3224 Peachtree Rd., N.E.	404 233-1569
MASSACHUSETTS	BOSTON	Richard Purinton, Inc.	11 Muzzey Street (Lexington 73)	617 VOLunteer 2-8300
NEW JERSEY	CAMDEN	Amphenol District Sales Office Robert Meade	6525 S. Crescent Blvd. Suite 212 (Pennsauken)	609 665-2870
NEW YORK	NEW YORK	Amphenol District Sales Office Glenn Omholt	310 Northern Blvd. (Great Neck, L.I.)	212 HUunter 2-4700
	SYRACUSE 3	Amphenol District Sales Office Larry McCahill	James Oak Bldg., Room 205 404 Oak Street	315 472-7529

GOVERNMENT CONTRACTS & SYSTEMS DEPARTMENT

ALABAMA	HUNTSVILLE	Tec-Sel, Inc., 43 Traylor Island	205 534-7304
CALIFORNIA	LOS ANGELES	Glenn H. Gross, Engineering Representative	213 STate 8-8560
DISTRICT OF COLUMBIA	WASHINGTON 5	Kenneth Collins, 17000 Ventura Blvd., Suite 306 (Encino) area manager	202 EXecutive 3-6223
ILLINOIS	CHICAGO	Carl E. Palmer, 625 Investment Bldg., 1511 K St., N.W. area manager	312 Columbus 1-2000
NEW JERSEY	FAIR LAWN	John E. Wilkinson, 2801 S. 25th Ave. (Broadview) manager	201 SWarthmore 7-6575
OHIO	DAYTON	Bennett Brachman, Fair Lawn Industrial Park area manager	513 223-3583 223-9602
		John E. Wilkinson, manager 333 W. First St., Suite 356	

AMPHENOL-BORG INTERNATIONAL OPERATIONS

CANADA	Amphenol Canada Limited, 349 Carlaw Avenue, Toronto 8, Ontario offices: Saedco Limited, 2277 Riverside Drive, Suite 209, Ottawa, Ontario Renfrew Electric Co. Limited, 5890 Monkland Avenue, Suite 203, Montreal, Quebec Radiovision Sales Limited, 351A—8th Avenue, S.W., Calgary, Alberta
ENGLAND	Amphenol-Borg Limited, Thanet Way, Tankerton, Whitstable, Kent Representatives in Norway, Sweden, Denmark, Finland, Spain and Portugal
JAPAN	Dai-Ichi Denshi Kabushiki Kaisha, #33, 4-Chome, Kamidori, Shibuya-ku, Tokyo
WEST GERMANY	Amphenol-Borg Electronics GmbH, 8024 Deisenhofen B. Munich Representatives in Italy, France, Switzerland, Austria, Belgium, Luxembourg, The Netherlands and Greece
OTHER INTERNATIONAL AREAS	Contact: International Operations Amphenol-Borg Electronics Corporation, 2801 South 25th Avenue, Broadview, Illinois Cable: Amphenol-Broadview